

Product Environmental Profile

Reference product name: H07V-R PASSEO 1G6 GREEN/YELLOW C100m



4,6E+02
kg CO₂ eq.
Global Warming




5,9E-02
kg Sb eq.
Depletion of abiotic resources - elements



1,5E+03
m³
Net use of Freshwater



1,0E+04
MJ
Total use of Primary Energy

PEP ecopassport N°:	NXNS-00140-V01.01-EN	Product Category Rules:	PEP-PCR-ed3-EN-2015 04 02
Verifier accreditation N°:	VH18	Product Specific Rules:	PSR-0001-ed3-EN-2015 10 16
Date of publication:	11-2021	Program information & documents:	www.pep-ecopassport.org
		Validity period:	5 years
<p>Independent verification of the declaration and data, in accordance with ISO 14025 : 2010</p> <p>Internal <input type="checkbox"/> External <input checked="" type="checkbox"/></p>			
<p>The PCR critical review was conducted by a panel of experts chaired by Philippe Osset (Solinnen).</p>			
<p>PEP are compliant with XP C08-100-1 :2016</p>			
<p>The elements of the present PEP cannot be compared with elements from another program.</p>			
<p>Compliant with ISO 14025: 2010 "Environmental labels and declarations - Type III environmental declarations".</p>			


REALIZED BY: S. PASQUELIN/M. VEAUX
101 Route d'Arnay - 71400 Autun - France
michael.veaux@nexans.com ☎ +33 (3) 85 86 63 00

<https://www.nexans.com/csr.html>



Nexans Corporate Social Responsibility commitment

Corporate Social Responsibility which is the confluence between environmental, economic and social aspects, is an integral part of the Nexans’s strategy. Nexans has been supporting the United Nations Global Compact since December 2008 and has implemented internal action plans to integrate Sustainable Development at all levels. It includes responsible governance, healthy and safe working environment for employees, reduced global carbon footprint through the Nexans Carbon Neutrality strategy.



Reference Product description

H07V-R PASSEO 1G6 GREEN/YELLOW C100m

H07V-R are insulated stranded copper conductors, used for fixed protected installations indoors for power supply or lightings (from offices, domestic or commercial buildings...) with voltage up to 1000V AC or 750V DC.

Product covered:

The aforementioned product belongs to the category Wires, Cables and Accessories of the Product Category Rules (PCR) from the PEP ecopassport® program.

The PEP concerns the product H07V-R PASSEO 1G6 GREEN/YELLOW C100m.

Functional unit:


To transmit energy expressed for 1A over a distance of 1km during 30 years and a 70% use rate, in accordance with the relevant standards, detailed in the data sheet available on our website www.nexans.com. Lifetime and use rate correspond to the Building - Residential / Tertiary / Industrial application as defined in the table given in Appendix 1 of the specific rules for wires, cables and accessories.

This PEP has been drawn up considering the following parameters:

- 1km for manufacturing, distribution and end-of-life stages
• 1km and 1A for the use stage

The potential impact of the use stage shall be calculated by the PEP user considering the real amperage through the product during the use phase by multiplying the impact by the square of the intensity. This PEP is valid in the intensity range taking into account the maximum allowable intensity.

Constituent materials



The total mass of the reference product and packaging is 83,1kg/km. Constituent materials are distributed as given in the graph.

Nexans has implemented necessary procedures to ensure product compliance with the relevant standards when products are put on the market.



Manufacturing



- The reference product is manufactured in France.
- The electricity mix model for the manufacturing stage is France, >1 kV.
- All Nexans sites in France have implemented a certified Environmental Management System according to ISO14001 standard.

Packaging designed to reduce environmental impacts:

- Packaging was designed according to the applicable standard (Directive 94/62/EC).
- The packaging considered to transport the reference product is a Wooden drum. It is considered to be used 1 time.
- The considered packaging is a PEFC™ (Program for the Endorsement of Forest Certification) certified wooden drum, ensuring responsible sourcing and sustainable forests management.

Distribution



The transportation scenario for the impact assessment of the distribution stage is intracontinental, considering:

- 3500 km covered by truck.

Installation



Installation processes for the reference product are considered out of the scope of the study, according to the Product Specific Rules document for "Wires, Cables and Accessories" from PEP ecopassport® program. Only packaging disposal is considered at this stage.

Use



The use scenario considers the operation of the reference product in Building - Residential / Tertiary / Industrial, with:

- Reference Lifetime (RLT) = 30 years
 - Current intensity (A): 1
 - Number of active conductor(s): 1
 - Use rate = 70 %
 - Cable resistance* (ohm/km): 3,08
- (*According to standard IEC 60228)

Considering the aforementioned hypotheses, the energy consumption over the RLT at use stage is 566,6 kWh/km.

This value is calculated for I=1 A. For the effective consumption of the cable installed, multiply the value given by the square of intensity.

- The electricity mix considered at use stage is Europe, ≤1 kV.
- No maintenance is necessary to ensure the operation of the cable during the considered reference lifetime.

The reference lifetime mentioned in this PEP corresponds to an average data used for impact calculation, taking into account the average time a cable might be installed in a system before being disposed. It CANNOT BE considered as an equivalent to the guaranteed product technical lifetime.

End-of-life



- The transportation scenario chosen for the impact analysis associated with end-of-life stage is 1000 km covered by truck.
- The assumed electricity mix model for end-of-life stage is Europe, >1 kV.

The cables are recycled through a grinding process for the separation of polymers and metal parts. It was considered that 100% of metals are recycled and 100% of other materials are landfilled.

Nexans has the know-how of cables recycling at their end-of-life through the structure named Nexans Recycling Services (recycling.services@nexans.com), to offer a complete solution for the recycling of polymers and metals.



III. ENVIRONMENTAL IMPACTS

The reference product H07V-R PASSEO 1G6 GREEN/YELLOW C100m belongs to the Product Category Rules (PEP-PCR-ed3-EN-2015 04 02) and Product Specific Rules (PSR-0001-ed3-EN-2015 10 16) from the PEP ecopassport® program. According to the PCR, the life cycle impact assessment of the reference product takes into account manufacturing, distribution, installation, use and end-of-life stages.

All the necessary hypotheses to evaluate the environmental impacts of the reference product lifecycle are presented in the previous sections (electricity mix models, use scenario, etc). The software used to perform the evaluation is EIME 5.9.1, with the Nexans-2021-06 database.

Representativeness: the study is representative of cable production in France with a intracontinental scenario for distribution. The electricity model for use is Europe, ≤1 kV and the model for end-of-life is Europe, >1 kV.

Impact results for 1000 m of H07V-R PASSEO 1G6 GREEN/YELLOW C100m

Mandatory indicators:

Environmental indicator/flows	Unit	Manufacturing	Distribution	Installation*	Use (for 1 A)	End-of-life	TOTAL (for 1 A)
Global Warming	kg CO ₂ eq.	1,59E+02	1,45E+01	1,15E+00	2,78E+02	9,89E+00	4,62E+02
Ozone Depletion	kg CFC-11 eq.	5,82E-05	2,93E-08	1,12E-08	1,81E-05	1,55E-06	7,79E-05
Acidification of soil and water	kg SO ₂ eq.	7,31E-01	6,50E-02	5,44E-03	1,16E+00	6,07E-02	2,02E+00
Eutrophication	kg PO ₄ ³⁻ eq.	1,09E-01	1,49E-02	5,90E-03	6,99E-02	1,05E-02	2,11E-01
Photochemical Ozone Creation	kg C ₂ H ₄ eq.	5,24E-02	4,62E-03	3,89E-04	6,36E-02	3,30E-03	1,24E-01
Depletion of abiotic resources - elements	kg Sb eq.	5,85E-02	5,79E-07	5,37E-08	2,41E-05	4,68E-07	5,85E-02
Total use of Primary Energy	MJ	4,46E+03	2,05E+02	1,53E+01	5,54E+03	1,75E+02	1,04E+04
Net use of Freshwater	m ³	4,73E+02	1,30E-03	4,61E-04	1,01E+03	1,78E-02	1,48E+03

Optional indicators:

Environmental indicator/flow complete name	Unit	Manufacturing	Distribution	Installation*	Use (for 1 A)	End-of-life	TOTAL (for 1 A)
Depletion of abiotic resources - fossil fuels	MJ	2,05E+03	2,03E+02	1,47E+01	3,15E+03	1,12E+02	5,53E+03
Water Pollution	m ³	1,60E+04	2,38E+03	1,70E+02	1,15E+04	8,54E+02	3,09E+04
Air Pollution	m ³	2,26E+05	5,93E+02	1,44E+02	1,19E+04	5,25E+02	2,40E+05
Use of renewable primary energy, excluding renewable primary energy resources used as raw materials	MJ	2,70E+02	2,73E-01	2,02E-01	7,05E+02	9,31E+00	9,85E+02
Use of renewable primary energy resources as raw materials	MJ	2,34E+02	0,00E+00	0,00E+00	0,00E+00	0,00E+00	2,34E+02
Total use of renewable primary energy resources	MJ	5,04E+02	2,73E-01	2,02E-01	7,05E+02	9,31E+00	1,22E+03
Use of non-renewable primary energy, excluding non-renewable primary energy resources used as raw materials	MJ	3,56E+03	2,04E+02	1,51E+01	4,84E+03	1,66E+02	8,78E+03
Use of non-renewable primary energy resources as raw materials	MJ	3,96E+02	0,00E+00	0,00E+00	0,00E+00	0,00E+00	3,96E+02
Total use of non-renewable primary energy resources	MJ	3,95E+03	2,04E+02	1,51E+01	4,84E+03	1,66E+02	9,18E+03
Use of renewable secondary fuels	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Use of non-renewable secondary fuels	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Use of secondary materials	kg	7,74E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	7,74E+00
Hazardous waste disposed	kg	5,39E+03	0,00E+00	4,34E-03	1,45E-01	5,44E-03	5,39E+03
Non-hazardous waste disposed	kg	5,21E+01	5,14E-01	1,77E+01	1,04E+03	4,16E+01	1,15E+03
Radioactive waste disposed	kg	6,02E-01	3,66E-04	1,40E-04	6,91E-01	1,94E-02	1,31E+00
Components for reuse	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Exported energy	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Materials for energy recovery	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Materials for recycling	kg	2,10E+00	0,00E+00	0,00E+00	0,00E+00	5,11E+01	5,32E+01

* Installation stage includes only packaging disposal. Impacts related to installation processes might be completed by the PEP user.